






DIMENSIONS



FEATURES

- IP66 / 67
- NEMA 4, 4x
- High Visibility Indicator Dome
- Compact Design
- SIL 3 Capable Option

TECHNICAL DATA

General Specifications

Body Material	Die cast aluminum
Indicator Dome	Polycarbonate
Coating	Grey polyester
Conduit Thread	1/2" NPT or M20
Conduit Quantity	2
Temperature Range	-13°F to 149°F (-25°C to 65°C)
Approx. Weight with 2 x SPDT	1.2 lbs / 0.5 kg
Mounting Pattern	VDI/VDE 3845
Terminal	4 or 8 Pole configurations
O-Rings	EPDM
Indicator Options	Open (yellow) Closed (red) Open (black) Closed (yellow) Open (green) Closed (red) Open (red) Closed (green)
Ratings	IP66/67 & NEMA 4, 4x
Certification	cULus on most models. CE Declaration
Hazardous Locations (Optional)	ATEX, IECEx, cULus for intrinsic safety

Mechanical Switches

Switch Type	SPDT	SPDT Low Power	Reed Switches
Switch Ratings	10A, 250V AC 1/2 HP, 250V AC 0.25A, 250V DC 0.5A, 125V DC	0.1A, 125V AC 0.1A, 30V DC 1mA, 4V AC/DC min	SPDT 180 mA, 110V AC 830 mA, 24V DC 20W max.
Max Number of Switches	2	2	2
Approvals	cULus, SIL 3 Capable	cULus, SIL 3 Capable	SIL 3 Capable

3-Wire DC Proximity Switches	PNP N.O.	PNP N.C.	NPN N.O.	NPN N.C.
Power Supply	Class 2	Class 2	Class 2	Class 2
Operating Voltage	10-30V DC	10-30V DC	10-30V DC	10-30V DC
Load Current	≤ 100 mA	≤ 100 mA	≤ 100 mA	≤ 100 mA
Current Consumption	≤ 15 mA	≤ 15 mA	≤ 15 mA	≤ 15 mA
Leakage Current	≤ 0.5 mA	≤ 0.5 mA	≤ 0.5 mA	≤ 0.5 mA
Voltage Drop	≤ 3V	≤ 3V	≤ 3V	≤ 3V
Max Number of Switches	2	2	2	2
Approvals	cULus	cULus	cULus	N/A


2-Wire Proximity Switches	140V N.O.	250V N.O.
Operating Voltage	20-140V AC 10-140V DC	20-250V AC 10-300V DC
Load Current	5-200 mA	≤ 100 mA
Leakage Current	≤ 0.8 mA	≤ 1.7 mA
Voltage Drop	≤ 7V	≤ 6V
Max Number of Switches	2	2
Approvals	N/A	N/A

NAMUR I.S. Switches	N.C.	
Current Consumption	≥ 3 mA (deactivated) ≤ 1 mA (activated)	UL/cUL
Max Power	64 mW	
Max Voltage	16 V	
Max Current	25 mA	
Switch	P+F NJ2-V3-N	ATEX
Effective Capacitance (C _e)	≤ 40 nF	IECEx
Effective Inductance (L _e)	≤ 50 µH	
Max Number of Switches	2	Ambient
Approval	cULus, ATEX, IECEx, SIL 3 Capable	



BRACKET

Bracket Type	NAMUR Pattern	Actuator Series	Actuator Size	VSM / Actuator	Std. Part No.
Single Piece	30 x 80	92 / 93	063 - 128	Imperial / Imperial	5B0000-22600534
				Imperial / Metric	5B0000-22630534
				Metric / Metric	5B0000-22650534
		98	All	Imperial / Metric	5B0000-22630534
				Metric / Metric	5B0000-22650534
Adjustable	30 x 80 or 30 x 130	92 / 93	063 - 210	Imperial / Imperial	5B0000-22601534
			063 - 255	Imperial / Metric	5B0000-22631534
				Metric / Metric	5B0000-22651534
		98	All	Imperial / Metric	5B0000-22631534
				Metric / Metric	5B0000-22651534

Single Piece Bracket




Adjustable Bracket for both 30x80 and 30x130 NAMUR mounting pads (fits all S92/93/98 actuators)



PART NUMBERING SYSTEM

5A000X-126XXXX / E X



HEADQUARTERS

Bray International, Inc.

13333 Westland East Blvd.

Houston, Texas 77041

Tel: 281.894.5454

bray.com

All statements, technical information, and recommendations in this bulletin are for general use only. Consult Bray representatives or factory for the specific requirements and material selection for your intended application. The right to change or modify product design or product without prior notice is reserved. Patents issued and applied for worldwide.

Bray® is a registered trademark of Bray International, Inc.

© 2022 Bray International. All rights reserved.

TM-1090_5A_aluminum_20221014